



INSTRUCTIONS FOR USE OF IGOAL

THE IGOAL IS INTENDED TO BE USED ONLY FOR FOOTBALL

1. ROLL IGOAL OUT OF BAG ONTO LEVEL SURFACE
2. MAKE SURE NET IS NOT CAUGHT ON HOSE OR CONNECTORS
3. USING THE PUMP PROVIDED (**AND ONLY THIS PUMP**) ATTACH TO VALVE WHICH IS SITUATED AT THE SIDE OF IGOAL (REAR OF CANTILEVER ON LARGER SIZES) MAKING SURE THAT THE VALVE(OR VALVES ON LARGER SIZES) IS TURNED FULLY **ANTI-CLOCKWISE**
4. PUT FEET ON THE FOOT PLATES ON EITHER SIDE OF THE PUMP FOR STABILITY
5. INFLATE FOR APPROX. 20-30 PUMPS (UNDER NORMAL CIRCUMSTANCES) AND SCREW THE VALVE CAP BACK ON TIGHT AFTER INFLATION
6. POP IGOAL UP INTO UPRIGHT POSITION
ON LARGER SIZES IT MAY BE NECESSARY FOR 2 PEOPLE TO CARRY OUT STAGE 6
7. ENSURE THAT THE IGOAL IS SECURED AT ALL TIMES BY MEANS OF THE APPROPRIATE SUPPLIED ANCHOR SYSTEM – DETAILS BELOW
8. IF FIXING ON GRASS – PLEASE USE THE GROUND PEGS PROVIDED – ATTACH PEGS PROVIDED AT FRONT AND BACK OF BOTH SIDE RETURNS
ON LARGER SIZES WITH CANTILEVER – PLACE 2 PEGS OVERLAPPED OVER EACH BLACK CANTILEVER
9. IF FIXING ON OTHER SURFACES i.e. ASTROTURF, CONCRETE OR INSIDE – PLEASE USE BAGS PROVIDED WHICH SHOULD BE FULLY FILLED WITH SOFT SAND TO ENSURE EVEN DISTRIBUTION OF WEIGHT – PLACE THE SANDBAGS OVER BOTH SIDE RETURNS
ON LARGER SIZES ALSO PLACE ONE SANDBAG OVER EACH BLACK CANTILEVER AS ABOVE
10. ONCE IN POSITION ADD MORE AIR USING PUMP PROVIDED TO PRESSURE REQUIRED
11. AFTER USE MAKE SURE THE AREA IS CLEAR OF ALL OBSTACLES AND PEOPLE BEFORE DEFLATION
12. REMOVE ALL PEGS OR SANDBAGS AFTER DEFLATION
13. TO DEFLATE THE IGOAL – TWIST VALVE FULLY **CLOCKWISE** AND PUSH TO RELEASE – THE IGOAL WILL FALL TO THE GROUND.
14. TWIST VALVE BACK **ANTI-CLOCKWISE** TO PREVENT AIR GOING BACK INTO IGOAL
15. IT IS RECOMMENDED THAT TO AID PACKING THAT THE PUMP IS RE-ATTACHED TO THE VALVE TURNED FULLY **CLOCKWISE** AND PUMP SEVERAL TIMES TO REMOVE ANY RESIDUAL AIR
16. PLACE IGOAL ON THE ROLL-OUT SECTION OF THE BAG
17. ROLL IGOAL BACK INTO THE BAG, PUT IT PUMP ON TOP OF ROLL-OUT SECTION. CLOSE USING TOP ZIPPERS FIRST, THEN SIDE ZIPPERS AFTER ANY PROTRUDING PARTS OF IGOAL ARE BACK INSIDE THE BAG.
18. THERE IS NO ONGOING MAINTENANCE SUBJECT TO PRODUCT NOT BEING MISUSED OR HANDLED CARELESSLY

www.redyset.com

GUARANTEE

This product is guaranteed for 12 months from the date of purchase against faulty materials or workmanship. During this period it will be replaced free of charge provided that:

1. **the fault is not limited to the net only;**
2. **the product is returned to original supplier with evidence of purchase in accordance with the claims procedure outlined on www.redyset.com ;**
3. **the product has been purchased by the user and not used for hire purposes;**
4. **the product has not been misused or handled carelessly; and**
5. **repairs have not been attempted**



www.redyset.com